

Step Tracking Receiver (STR)

Beacon tracking receiver
for satcom antenna tracking

The new generation STR tracking receiver is an essential element in the pursuit of both commercial and military satellites. These satellites can be either geostationary (GEO) or in low earth orbit (LEO) or medium earth orbit (MEO). This tracking receiver uses the step-by-step technique, searching for the maximum received beacon signal to maintain the axis of the antenna beam in the direction of the satellite, despite the movement of the satellite or station. An anti-sideband function prevents the receiver from locking to the sidebands of the signal to be tracked.



FEATURES

- Delivers DC output voltage proportional to received signal strength
- Accepts PM or BPSK input modulated carrier and includes an anti-sideband system
- Performance advantage remote control/monitoring is achieved via RS232 and ethernet

ISO9001/EN9100/AS9100/JISQ9100

EUROPEAN CONFORMITY

EN 62368-1

EN 301489-1 V2 . 2 . 0

Input

Impedance	50 Ω
VSWR	≤ 2.0
Noise factor	13 dB typ.
Input frequency	cf. models
Dynamic range	-100 to -30 dBm

M&C output

RJ15 output interface	TCP/IP
RS232 output interface	—
Alarm signal	One dry loop
Lock information	One dry loop

Power supply

Voltage	110 V / 250 V
Frequency	48 to 63 Hz
Consumption	20 VA max

Mode coherent

Acquisition Threshold	C/N0: ≥ 35 dBc/Hz
Acquisition Time	<1 s (PM)
Search Range	± 25 kHz / ± 50 kHz / ± 100 kHz / ± 150 kHz with anti-sideband rejection facility

No-coherent mode

Tracking on power in a configured bandwidth
10kHz, 50kHz, 150kHz, 500kHz, 1.5MHz, 5MHz
(any kind of signal or noise)

AGC output

Voltage dynamic	0.5 V/dB (0 to 10 V max)
Signal dynamic	20 dB
Connector type	BNC (F)
Impedance	1 k Ω

External frequency ref.

Frequency	10 MHz
Connector	BNC (F)
Expected value	0 dBm ± 3 dB
VSWR	< 1.5 – 50 Ω

Mechanical characteristics

Drawer	19" $\times$ 1 U $\times$ 310 mm
Weight	< 4.5 kg
Consumption	20 VA max

Environmental conditions

Operating	+5 °C to +50 °C (non-condensing, 95% humidity at 30 °C)
Non-operating	-20 °C to +71 °C (non-condensing, 95% humidity at 40 °C)
Vibrations	± 1 mm from 5 to 16 Hz / 1 g from 16 to 55 Hz
Shocks	1/2 sinus 15 g, 11 ms on the 3 axes

Models

STR-L	950 – 2,150 MHz
STR-X	7.25 – 7.75 GHz
STR-Ku	10.7 – 12.75 GHz

HEAD OFFICE:

Exail Aerospace SAS

ZAC de Saint Martin du Touch
6 Impasse Alice Guy
31300 Toulouse – FRANCE
+33 5 62 11 17 17 | contact-aerospace@exail.com

www.exail.com

exail